






**EURO mortise**



**ANSI mortise**



**Installation diagram**



## Technical features

|                                      |   |
|--------------------------------------|---|
| <b>Intended use</b>                  | Standalone battery powered contactless electronic access control for guest room door installation.                  |
| <b>Form factor</b>                   | RFID reader integrated into the external plate. Battery holder integrated into the internal plate.                  |
| <b>Credentials</b>                   | Contactless RFID ISO 14443B/Mifare ISO 14443A, NFC ready.<br>Lock wake-up function activated by card from max 2 cm. |
| <b>Operating temperature</b>         | From -10°C to 70°C (with specific batteries).   |
| <b>Data encryption</b>               | 3DES-AES encryption.  |
| <b>Audit trail</b>                   | Last 500 events.  |
| <b>Privacy</b>                       | Mechanical privacy function activated by a knob on the internal plate.  |
| <b>Emergency override detection</b>  | Mechanical emergency opening. Event detection and registration into the lock audit trail.                           |
| <b>Flashing signal</b>               | Multicolor LED on external plate for battery level and privacy status.  |
| <b>Battery</b>                       | 4 x 1.5V AAA alkaline.  |
| <b>Battery durability</b>            | 20,000 cycles (depending on operating conditions).  |
| <b>External plate</b>                | 263 mm (L) x 68 mm (W) x 71 mm (D including handle).  |
| <b>Internal plate</b>                | 263 mm (L) x 68 mm (W) x 71 mm (D including handle).  |
| <b>Weight</b>                        | Packed: 2.1 kg (mortise lock, spindles, external and internal plates, escutcheons, handles, single cylinder).       |
| <b>Material</b>                      | External/Internal plates in aluminum.   |
| <b>Plastic</b>                       | Nylon. Cover plate available in black version.  |
| <b>Finishes</b>                      | Satin Silver.   |
| <b>Handles</b>                       | Classic.  |
| <b>Spindle size</b>                  | 8 mm.   |
| <b>Mechanical emergency cylinder</b> | Euro profile half cylinder concealed under plastic cover.<br>The cover is removable making it drop downward.        |
| <b>Mechanical lock</b>               | Euro and ANSI versions available.   |
| <b>Backset</b>                       | Euro centre distance: 55 mm*72 mm. ANSI inverted, centre distance: 62 mm*95 mm.                                     |
| <b>Door thickness</b>                | 35 - 90 mm.   |
| <b>Life cycle</b>                    | 200,000 cycles.   |
| <b>Installation</b>                  | Compatible with electric screwdrivers i.e. high torque.   |
| <b>Norms and regulations</b>         | Compatible with fire rated doors up to 60 minutes in compliance with European standards EN1634 e UL.                |
| <b>Management system</b>             | Encoder operated with NFC mouse and service cards. Compatible with CISA AERO web application.                       |
| <b>Retrofit underplate</b>           | A metal underplate mounted between the door and the CISA eGO handle plate to cover the existing holes.              |

Please refer to the eGO Installation Manual for further details on door and frame dimension requirements for a correct installation.

### About Allegion™

Allegion (NYSE: ALLE) is a global pioneer in safety and security, with leading brands like CISA®, Interflex®, LCN®, Schlage® and Von Duprin®. Focusing on security around the door and adjacent areas, Allegion produces a range of solutions for homes, businesses, schools and other institutions. Allegion is a \$2 billion company, with products sold in almost 130 countries.

For more, visit [allegion.com](http://allegion.com)

 **BRICARD** ■ **Briton** ■  **CISA** ■  **interflex**

CISA S.p.A.  
Via Oberdan, 42  
48018 Faenza (RA) Italy  
Tel. +39.0546.677111  
Fax +39.0546.677150  
[cisa.sales@allegion.com](mailto:cisa.sales@allegion.com)  
cisa.com  
cisahotels.com

@cisalocks

