




Technical features:

- Carbonitrided solid steel body, with chemical anti-corrosion nickel-plating treatment
- Hardened steel shackle, with chemical nickel-plating treatment
- **The removable cylinder can be either rekeyed or replaced**
- Carbonitrided steel plug protection plate
- Carbonitrided steel cylinder protection plate, with chemical nickel-plating treatment
- Desmopan impact resistant protection device (for the 28050 series)
- LIM patented key profile

Supplied as standard:

- 2 keys

Type	Description	Key item					Unit weight	Pieces	ITEM			
		A	C	D	L	S			Type	Dim.	Hand	Fin.




- Key removable in locked position only

55	25,0	11,0	25,0	25,0	5	1 00401 00 1	0,565	6	1	28050	55 0
55	25,0	11,0	45,0	25,0	5	1 00401 00 1	0,601	6	1	28050	56 0
55	26,0	11,0	65,0	25,0	5	1 00401 00 1	0,610	6	1	28050	57 0
70	31,0	14,0	25,0	26,0	5	1 00401 00 1	0,880	6	1	28050	70 0
70	31,0	14,0	45,0	26,0	5	1 00401 00 1	0,927	6	1	28050	71 0
70	31,0	14,0	65,0	26,0	5	1 00401 00 1	0,954	6	1	28050	72 0



- Clam packing

55	25,0	11,0	25,0	25,0	5	1 00401 00 1	0,578	6	1	28055	55 0
55	25,0	11,0	45,0	25,0	5	1 00401 00 1	0,608	6	1	28055	56 0
55	26,0	11,0	65,0	25,0	5	1 00401 00 1	0,636	6	1	28055	57 0
70	31,0	14,0	25,0	26,0	5	1 00401 00 1	0,870	6	1	28055	70 0
70	31,0	14,0	45,0	26,0	5	1 00401 00 1	0,929	6	1	28055	71 0
70	31,0	14,0	65,0	26,0	5	1 00401 00 1	0,971	6	1	28055	72 0



- Key removable in locked position only


62	25,0	11,0	25,0	25,0	5	1 00401 00 1	0,745	6	1	28350	62 0
73	31,0	14,0	28,0	28,0	5	1 00401 00 1	1,116	6	1	28350	73 0

Type	Description	Key item					Unit weight	Pieces	ITEM				
		A	C	D	L	S			Plns	Type	Dim.	Hand	Fin.



• Clam packing

62	25,0	11,0	25,0	25,0	5	1 00401 00 1	0,768	6	1	28355	62	0
73	31,0	14,0	28,0	28,0	5	1 00401 00 1	1,140	6	1	28355	73	0



66	20,0	10,0	11,0	25,0	5	1 00401 00 1	0,685	6	1	28550	66	0
66	18,0	14,0	17,5	28,0	5	1 00401 00 1	0,837	6	1	28550	67	0
75	27,0	12,0	13,5	28,0	5	1 00401 00 1	0,852	6	1	28550	75	0
84	36,0	12,0	17,5	28,0	5	1 00401 00 1	0,970	6	1	28550	84	0
84	36,0	14,0	17,5	28,0	5	1 00401 00 1	0,983	6	1	28550	85	0



• Clam packing

66	20,0	10,0	11,0	25,0	5	1 00401 00 1	0,745	6	1	28555	66	0
66	18,0	14,0	17,5	28,0	5	1 00401 00 1	0,855	6	1	28555	67	0
75	27,0	12,0	13,5	28,0	5	1 00401 00 1	0,905	6	1	28555	75	0
84	36,0	12,0	17,5	28,0	5	1 00401 00 1	1,018	6	1	28555	84	0
84	36,0	14,0	17,5	28,0	5	1 00401 00 1	1,009	6	1	28555	85	0



Technical features:


- Patented system
- Registered key
- Carbonitrided solid steel body, with chemical nickel-plating corrosion treatment
- Hardened steel shackle, with chemical nickel-plating treatment
- Carbonitrided steel cylinder protection plate, with chemical nickel-plating treatment
- **The removable cylinder can be either rekeyed or replaced**
- **KEY**
 - In nickel silver alloy
 - numbered on key bow

Supplied as standard:

- 2 keys
 - CODE CARD
- Key is protected by a Shape trademark
BO2004C000170


SP

Type	Description	Key item						Unit weight	Pieces	ITEM			
		A	C	D	L	S	Pins			Kg	Type	Dim.	Hand




• Key removable in locked position only

55	25,0	11,0	25,0	25,0	6	1 00450 01 1	0,570	6	1	28052	55	0
55	25,0	11,0	45,0	25,0	6	1 00450 01 1	0,600	6	1	28052	56	0
55	26,0	11,0	65,0	25,0	6	1 00450 01 1	0,635	6	1	28052	57	0
70	31,0	14,0	25,0	26,0	6	1 00450 01 1	0,870	6	1	28052	70	0
70	31,0	14,0	45,0	26,0	6	1 00450 01 1	0,920	6	1	28052	71	0
70	31,0	14,0	65,0	26,0	6	1 00450 01 1	0,970	6	1	28052	72	0



• Key removable in locked position only

73	31,0	14,0	28,0	28,0	6	1 00450 01 1	1,140	6	1	28352	73	0
----	------	------	------	------	---	--------------	-------	---	---	-------	----	---



66	18,0	14,0	17,5	28,0	6	1 00450 01 1	0,720	6	1	28552	67	0
75	27,0	12,0	13,5	28,0	6	1 00450 01 1	0,870	6	1	28552	75	0
84	36,0	12,0	17,5	28,0	6	1 00450 01 1	0,985	6	1	28552	84	0
84	36,0	14,0	17,5	28,0	6	1 00450 01 1	1,000	6	1	28552	85	0



Astral


Technical features:

- Carbonitrided solid steel body, with chemical anti-corrosion nickel-plating treatment
- Hardened steel shackle, with chemical nickel-plating treatment
- Carbonitrided steel cylinder protection plate, with chemical nickel-plating treatment
- The removable cylinder can be either rekeyed or replaced
- KEY:
- flat reversible keys
- numbered on key bow

Supplied as standard:


- 2 keys
- Code Card

Type	Description	Key item						Unit weight	Pieces	ITEM			
		A	C	D	L	S	Pins			Type	Dim.	Hand	Fin.




• Key removable in locked position only

55	25,0	11,0	25,0	25,0	10	1 00620 01 0	0,553	6	1	28053	55	0
55	25,0	11,0	45,0	25,0	10	1 00620 01 0	0,586	6	1	28053	56	0
55	26,0	11,0	65,0	25,0	10	1 00620 01 0	0,610	6	1	28053	57	0
70	31,0	14,0	25,0	26,0	10	1 00620 01 0	0,854	6	1	28053	70	0
70	31,0	14,0	45,0	26,0	10	1 00620 01 0	0,903	6	1	28053	71	0
70	31,0	14,0	65,0	26,0	10	1 00620 01 0	0,954	6	1	28053	72	0



• Key removable in locked position only

62	25,0	11,0	25,0	25,0	10	1 00620 01 0	0,745	6	1	28353	62	0
73	31,0	14,0	28,0	28,0	10	1 00620 01 0	1,116	6	1	28353	73	0



66	20,0	10,0	11,0	25,0	10	1 00620 01 0	0,677	6	1	28553	66	0
66	18,0	14,0	17,5	28,0	10	1 00620 01 0	0,837	6	1	28553	67	0
75	27,0	12,0	13,5	28,0	10	1 00620 01 0	0,843	6	1	28553	75	0
84	36,0	12,0	17,5	28,0	10	1 00620 01 0	0,955	6	1	28553	84	0
84	36,0	14,0	17,5	28,0	10	1 00620 01 0	0,983	6	1	28553	85	0




Technical features:

- Patented system: key with incorporated mobile element
- Security Card: authorised duplication by Cisa or Cisa Solution Partner
- Carbonitrided solid steel body, with chemical nickel-plating corrosion treatment
- Hardened steel shackle, with chemical nickel-plating treatment
- Carbonitrided steel cylinder protection plate, with chemical nickel-plating treatment
- The removable cylinder can be either rekeyed or replaced
- KEY:
 - flat reversible keys, with incorporated mobile element
 - in nickel silver alloy
 - numbered on key bow

Supplied as standard:


- 2 keys
- SECURITY CARD

Type	Description	Key item						Kg	Pieces	ITEM			
		A	C	D	L	S	Pins			Type	Dim.	Hand	Fin.




• Key removable in locked position only

55	25,0	11,0	45,0	25,0	15	1 00770 00 0	0,586	6	1 28058 56 0
55	26,0	11,0	65,0	25,0	15	1 00770 00 0	0,610	6	1 28058 57 0
70	31,0	14,0	25,0	26,0	15	1 00770 00 0	0,854	6	1 28058 70 0
70	31,0	14,0	45,0	26,0	15	1 00770 00 0	0,903	6	1 28058 71 0
70	31,0	14,0	65,0	26,0	15	1 00770 00 0	0,954	6	1 28058 72 0



• Key removable in locked position only

62	25,0	11,0	25,0	25,0	15	1 00770 00 0	0,745	6	1 28358 62 0
73	31,0	14,0	28,0	28,0	15	1 00770 00 0	0,745	6	1 28358 73 0



66	20,0	10,0	11,0	25,0	15	1 00770 00 0	0,677	6	1 28558 66 0
66	18,0	14,0	17,5	28,0	15	1 00770 00 0	0,837	6	1 28558 67 0
75	27,0	12,0	13,5	28,0	15	1 00770 00 0	0,843	6	1 28558 75 0
84	36,0	12,0	17,5	28,0	15	1 00770 00 0	0,995	6	1 28558 84 0
84	36,0	14,0	17,5	28,0	15	1 00770 00 0	0,974	6	1 28558 85 0



RS3


Technical features:

- Patented system: key with incorporated mobile element
- Security Card: authorised duplication by Cisa onyl
- Carbonitrided solid steel body, with chemical nickel-plating corrosion treatment
- Hardened steel shackle, with chemical nickel-plating treatment
- Carbonitrided steel cylinder protection plate, with chemical nickel-plating treatment
- The removable cylinder can be either rekeyed or replaced
- KEY
 - flat reversible keys, with incorporated mobile element
 - in nickel silver alloy
 - numbered on key bow

Supplied as standard:


- 2 keys
- SECURITY CARD

Type	Description	Key item					Unit weight	Pieces	ITEM			
		A	C	D	L	S			Pins	Type	Dim.	Hand




• Key removable in locked position only

55	25,0	11,0	25,0	25,0	15	1 00800 00 0	0,553	6	1	28059	55	0	00	CL
70	31,0	14,0	25,0	26,0	15	1 00800 00 0	0,854	6	1	28059	70	0	00	CL
70	31,0	14,0	45,0	26,0	15	1 00800 00 0	0,903	6	1	28059	71	0	00	CL
70	31,0	14,0	65,0	26,0	15	1 00800 00 0	0,954	6	1	28059	72	0	00	CL



• Key removable in locked position only

62	25,0	11,0	25,0	25,0	15	1 00800 00 0	0,745	6	1	28359	62	0	00	CL
73	31,0	14,0	28,0	28,0	15	1 00800 00 0	1,150	6	1	28359	73	0	00	CL



66	20,0	10,0	11,0	25,0	15	1 00800 00 0	0,677	6	1	28559	66	0	00	CL
66	18,0	14,0	17,5	28,0	15	1 00800 00 0	0,837	6	1	28559	67	0	00	CL
75	27,0	12,0	13,5	28,0	15	1 00800 00 0	0,843	6	1	28559	75	0	00	CL
84	36,0	12,0	17,5	28,0	15	1 00800 00 0	0,995	6	1	28559	84	0	00	CL
84	36,0	14,0	17,5	28,0	15	1 00800 00 0	0,974	6	1	28559	85	0	00	CL