



**Technical features:**

- Laquered polished brass removable faceplate and striker
- Zinc-plated steel case
- Reversible, nickel-plated silent action latch
- Nickel-plated bolt for latch dead-locking (if provided)
- Nickel-plated cut-resistant dead-bolt, with a 25 mm. protrusion
- Anti-corrosion galvanised internal components

**Supplied as standard:**

- Striking plate
- Fixing screws
- Instruction sheet

**Finishes:**

- ON REQUEST: Satin stainless steel faceplate and striker (fin 20)

**Standards:**


- Locks with satin stainless steel faceplate and striker (finish 20), are certified fire-resistant by the American Underwrite Laboratories (UL LISTED R 14945(N))
- CE mark in compliance with the directive 89/106/CEE, only for item with (fin. 20)
- Standard reference:
  - UNI EN 179
  - UNI EN 1125
  - UNI EN 12209

**Hand:**  
0 = Non-handed

**Cylinder to be ordered separately**




Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM				
								Type	Dim.	Hand	Fin.	Pers. Spec.




- For entrance doors
- Dead-bolt and dead-locking latch
- OPERATION:  
the latch-bolt is operated by handle or cylinder from either side  
The dead-bolt is operated by cylinder from either side
- SUPPLIED AS STANDARD:  
Square striking plate item 1.06106.20.0

1	85	22	60	0,910	1	1	52710 60 0				
1	85	22	70	1,000	1	1	52710 70 0				
1	85	22	80	1,050	1	1	52710 80 0				
1	85	22	90	1,100	1	1	52710 90 0				




- For entrance doors
- Dead-bolt and dead-locking latch
- OPERATION:  
the latch-bolt is operated by handle or cylinder from either side  
The dead-bolt is operated by cylinder from either side
- SUPPLIED AS STANDARD:  
Square striking plate item 1.06106.25.0

1	85	22	60	0,950	1	1	52711 60 0				
1	85	22	70	1,000	1	1	52711 70 0				
1	85	22	80	1,050	1	1	52711 80 0				
1	85	22	90	1,100	1	1	52711 90 0				



- For bathroom
- Dead-bolt and latch
- OPERATION:  
the latch-bolt is operated by handle from either side  
The dead-bolt is operated by a 8 mm spindle
- SUPPLIED AS STANDARD:  
Square striking plate item 1.06155.20.0






1	85	22	60	0,950	1	1	52730 60 0				
1	85	22	70	1,000	1	1	52730 70 0				
1	85	22	80	1,050	1	1	52730 80 0				
1	85	22	90	1,100	1	1	52730 90 0				



- For bathroom
- Dead-bolt and latch
- OPERATION:  
the latch-bolt is operated by handle from either side  
The dead-bolt is operated by a 8 mm spindle
- SUPPLIED AS STANDARD:  
Round striking plate item 1.06155.25.0

1	85	22	60	0,950	1	1	52731 60 0				
1	85	22	60	1,000	1	1	52731 70 0				
1	85	22	80	1,050	1	1	52731 80 0				
1	85	22	90	1,100	1	1	52731 90 0				

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight 	Pieces 	ITEM				
								Type	Dim.	Hand	Fin.	Pers. Spec.
	<ul style="list-style-type: none"> <li>• For passage doors</li> <li>• Latch-bolt only</li> <li>• OPERATION: The latch-bolt is operated by handle from either side</li> <li>• SUPPLIED AS STANDARD: Square striking plate item 1.06156.20.0</li> </ul>	22	60	0,900	1	1	52750	60	0			
		22	70	1,000	1	1	52750	70	0			
		22	80	0,835	1	1	52750	80	0			
		22	90	1,100	1	1	52750	90	0			
	<ul style="list-style-type: none"> <li>• For passage doors</li> <li>• Latch-bolt only</li> <li>• OPERATION: The latch-bolt is operated by handle from either side</li> <li>• SUPPLIED AS STANDARD: Round striking plate item 1.06156.25.0</li> </ul>	22	60	0,900	1	1	52751	60	0			
		22	70	1,000	1	1	52751	70	0			
		22	80	1,000	1	1	52751	80	0			
		22	90	1,100	1	1	52751	90	0			
	<ul style="list-style-type: none"> <li>• For external doors</li> <li>• Dead-locking latch-bolt only</li> <li>• OPERATION: The latch-bolt is operated by handle or cylinder from either side The outside handle must be de-activated</li> <li>• SUPPLIED AS STANDARD: Square striking plate item 1.06158.20.0</li> </ul>	85	22	60	0,900	1	1	52755	60	0		
		85	22	70	1,000	1	1	52755	70	0		
		85	22	80	1,050	1	1	52755	80	0		
		85	22	90	1,100	1	1	52755	90	0		
	<ul style="list-style-type: none"> <li>• For external doors</li> <li>• Dead-locking latch-bolt only</li> <li>• OPERATION: The latch-bolt is operated by handle or cylinder from either side The outside handle must be de-activated</li> <li>• SUPPLIED AS STANDARD: Round striking plate item 1.06158.25.0</li> </ul>	85	22	60	0,950	1	1	52756	60	0		
		85	22	70	1,000	1	1	52756	70	0		
		85	22	80	1,050	1	1	52756	80	0		
		85	22	90	1,100	1	1	52756	90	0		
	<ul style="list-style-type: none"> <li>• FUNCTION TYPE B:</li> <li>• For panic function doors (for the suitable panic exit device to install, see the relevant catalogue)</li> <li>• Latch only with antipicking device</li> <li>• Split square spindle</li> <li>• Reversible panic function</li> <li>• The outside handle can be disactivated with the key</li> <li>• Outside: the latch can be operated with the handle, the key activates/disactivates the handle</li> <li>• Inside: the latch can be operated with the handle or the panic exit device, the key activates/disactivates the outside handle</li> <li>• Note: when the door is opened from the inside with the handle or the panic exit device, the outside handle remains disactivated after the door is closed (in stand-by)</li> </ul>	85	22	60	0,900	1	1	52760	60	0		
		85	22	70	1,000	1	1	52760	70	0		
		85	22	80	1,050	1	1	52760	80	0		
		85	22	90	1,050	1	1	52760	90	0		

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM				
								Type	Dim.	Hand	Fin.	Pers. Spec.
 <ul style="list-style-type: none"> <li>• <b>FUNCTION TYPE B:</b></li> <li>• For panic function doors (for the suitable panic exit device to install, see the relevant catalogue)</li> <li>• Latch only with antipicking device</li> <li>• Split square spindle</li> <li>• Reversible panic function</li> <li>• The outside handle can be disactivated with the key</li> <li>• Outside: the latch can be operated with the handle, the key activates/disactivates the handle</li> <li>• Inside: the latch can be operated with the handle or panic exit device, the key activates/disactivates the outside handle</li> <li>• Note: when the door is opened from the inside with the handle or the panic exit device, the outside handle remains disactivated after the door is closed (in stand-by)</li> </ul>	85	22	60	0,885	1	1	<b>52761 60 0</b>					
	85	22	70	1,000	1	1	<b>52761 70 0</b>					
	85	22	80	1,050	1	1	<b>52761 80 0</b>					
	85	22	90	1,100	1	1	<b>52761 90 0</b>					
 <ul style="list-style-type: none"> <li>• For cabinet doors</li> <li>• Dead-bolt only</li> <li>• OPERATION: The dead-bolt is operated by cylinder from either side</li> <li>• SUPPLIED AS STANDARD: Square striking plate item 1.06159.20.0</li> </ul>	1	22	60	0,950	1	1	<b>52780 60 0</b>					
	1	22	70	1,000	1	1	<b>52780 70 0</b>					
	1	22	80	1,050	1	1	<b>52780 80 0</b>					
	1	22	90	0,000	1	1	<b>52780 90 0</b>					
 <ul style="list-style-type: none"> <li>• For cabinet doors</li> <li>• Dead-bolt only</li> <li>• OPERATION: The dead-bolt is operated by cylinder from either side</li> <li>• SUPPLIED AS STANDARD: Round striking plate item 1.06159.25.0</li> </ul>	1	22	70	1,000	1	1	<b>52781 60 0</b>					
	1	22	70	1,000	1	1	<b>52781 70 0</b>					
	1	22	80	1,050	1	1	<b>52781 80 0</b>					
	1	22	90	1,100	1	1	<b>52781 90 0</b>					
 <ul style="list-style-type: none"> <li>• <b>FUNCTION TYPE A:</b> for panic function doors (for the suitable panic exit device to install, see the relevant catalogue)</li> <li>• Through square spindle</li> <li>• The deadbolt is automatically released when closing the door</li> <li>• Outside: latch and dead-bolt are operated only with the key</li> <li>• Inside: latch and dead-bolt are operated with the key, the handle or the panic exit device</li> </ul>	1	85	22	60	0,950	1	1	<b>52840 60 0</b>				
	1	85	22	70	1,000	1	1	<b>52840 70 0</b>				
	1	85	22	80	1,050	1	1	<b>52840 80 0</b>				
	1	85	22	90	1,100	1	1	<b>52840 90 0</b>				
 <ul style="list-style-type: none"> <li>• <b>FUNCTION TYPE A:</b> for panic function doors (for the suitable panic exit device to install, see the relevant catalogue)</li> <li>• Through square spindle</li> <li>• The deadbolt is automatically released when closing the door</li> <li>• Outside: latch and dead-bolt are operated only with the key</li> <li>• Inside: latch and dead-bolt are operated with the key, the handle or the panic exit device</li> </ul>	1	85	22	60	0,950	1	1	<b>52860 60 0</b>				
	1	85	22	70	1,000	1	1	<b>52860 70 0</b>				
	1	85	22	80	1,050	1	1	<b>52860 80 0</b>				
	1	85	22	90	1,100	1	1	<b>52860 90 0</b>				

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight 	Pieces 	ITEM					
								Type	Dim.	Hand	Fin.	Pers. Spec.	
	<ul style="list-style-type: none"> <li>• FUNCTION TYPE A:</li> <li>• for panic function doors (for the suitable panic exit device to install, see the relevant catalogue)</li> <li>• Latch and dead bolt with antipicking device</li> <li>• Through square spindle</li> <li>• Outside: latch and dead-bolt are operated only with the key</li> <li>• Inside: latch and dead-bolt are operated with the key, the handle or the panic exit device</li> </ul>	1	85	22	60	0,950	1	1	52842	60	0		
		1	85	22	70	1,000	1	1	52842	70	0		
		1	85	22	80	1,050	1	1	52842	80	0		
		1	85	22	90	1,100	1	1	52842	90	0		
	<ul style="list-style-type: none"> <li>• FUNCTION TYPE A:</li> <li>• for panic function doors (for the suitable panic exit device to install, see the relevant catalogue)</li> <li>• Latch and dead bolt with antipicking device</li> <li>• Through square spindle</li> <li>• Outside: latch and dead-bolt are operated only with the key</li> <li>• Inside: latch and dead-bolt are operated with the key, the handle or the panic exit device</li> </ul>	1	85	22	60	0,950	1	1	52862	60	0		
		1	85	22	70	1,000	1	1	52862	70	0		
		1	85	22	70	1,050	1	1	52862	80	0		
		1	85	22	70	1,050	1	1	52862	90	0		
	<ul style="list-style-type: none"> <li>• FUNCTION TYPE D:</li> <li>• for panic function doors (for the suitable panic exit device to install, see the relevant catalogue)</li> <li>• Split square spindle</li> <li>• Reversible panic function</li> <li>• Outside: the latch can be operated with the handle</li> <li>• Inside: latch and dead-bolt are operated with the handle or the panic exit device</li> <li>• The key operates only the dead-bolt from either side</li> <li>• Note: when the door is opened from the inside with the handle or the panic exit device, the dead-bolt remains withdrawn after closing the door and the outside handle remains activated and can withdraw the latch (door open)</li> </ul>	1	85	22	60	0,950	1	1	52844	60	0		
		1	85	22	70	1,000	1	1	52844	70	0		
		1	85	22	80	1,050	1	1	52844	80	0		
		1	85	22	90	1,100	1	1	52844	90	0		
	<ul style="list-style-type: none"> <li>• FUNCTION TYPE D:</li> <li>• for panic function doors (for the suitable panic exit device to install, see the relevant catalogue)</li> <li>• Split square spindle</li> <li>• Reversible panic function</li> <li>• Outside: the latch can be operated with the handle</li> <li>• Inside: latch and dead-bolt are operated with the handle or the panic exit device</li> <li>• The key operates only the dead-bolt from either side</li> <li>• Note: when the door is opened from the inside with the handle or the panic exit device, the dead-bolt remains withdrawn after closing the door and the outside handle remains activated and can withdraw the latch (door open)</li> </ul>	1	85	22	60	0,950	1	1	52864	60	0		
		1	85	22	70	1,000	1	1	52864	70	0		
		1	85	22	80	1,050	1	1	52864	80	0		
		1	85	22	90	1,100	1	1	52864	90	0		