



Technical features:

- Zinc plated steel case
- Nickel-plated latch, roller and dead-bolt
- Latch or reversible latch/bolt (where this is provided for)
- Current absorption 3,1A
- Voltage 12 V ac CE

Supplied as standard:

- Pair of nylon roses item 1.06012.01.0
- Lock and cylinder fixing screws
- Instruction sheet

On request:

- Special striker plates (see Vademecum)
- Cylinder with pin key series 02400
- Cylinder protective rose item 1.06460.00.0
- Cylinder with pin key series 02400
- Mechanical control button item 1.06110.10.0

Certification:

- This lock series is certified according to the European standard EN 15685:09
 - Security class 4 (700 Kg side thrust and 500 Kg front thrust resistance)
- Suitable for doors certified to EN1627:2011 up to WK/RC 2 resistance class


Hand:

0 = Non-handed

Cylinder to be ordered separately



Type	Description	Locking points	Throws	Centre Distance	Faceplate	Backset	Unit weight	Pieces	ITEM			
									Type	Dim.	Hand	Fin.




- Black painted steel adjustable U-shaped faceplate 24 x 7 mm, 2,600 mm.
 - upper adjustment 650 mm.
 - lower adjustment 150 mm.
- 10.5 to 16.5 adjustable latch bolt and bolt
- 3 lateral dead-bolts
- Faceplate cover nylon plugs
- 12 V ca CE

3	1	85	24	25	3,500	1	1	16425	25	0
3	1	85	24	30	3,500	1	1	16425	30	0
3	1	85	24	35	3,500	1	1	16425	35	0

- Stainless steel adjustable U-shaped faceplate 24 x 7 mm., 2.300 mm.
 - upper adjustment 350 mm.
 - lower adjustment 150 mm.
- 10.5 to 16.5 mm. adjustable latch and piston
- 3 lateral dead-bolts
- 12 V ca CE


3	1	85	24	25	3,780	1	1	16625	25	0
3	1	85	24	30	3,800	1	1	16625	30	0
3	1	85	24	35	3,820	1	1	16625	35	0

Type	Description	Locking points	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM				
									Type	Dim.	Hand	Fin.	Pers.



- Black lacquered steel adjustable U-shaped faceplate
24 x 7 mm., 2.600 mm.
upper adjustment 650 mm.
lower adjustment 150 mm.
- 3 lateral dead-bolts
- Nylon faceplate cover plugs


3	1	24	25	3,600	1	1	46420	25	0				
3	1	24	30	3,620	1	1	46420	30	0				
3	1	24	35	3,640	1	1	46420	35	0				



- Black lacquered steel adjustable U-shaped faceplate
24 x 7 mm., 2.600 mm.
upper adjustment 650 mm.
lower adjustment 150 mm.
 - 11 to 17 mm. adjustable latch and piston
 - 3 lateral dead-bolts
 - Nylon faceplate cover plugs
-
- Stainless steel adjustable U-shaped faceplate
24 x 7 mm., 2.300 mm.
upper adjustment 350 mm.
lower adjustment 150 mm.
 - 11 to 17 mm. adjustable latch
 - 3 lateral dead-bolts


3	1	85	24	25	3,500	1	1	46425	25	0			
3	1	85	24	30	3,500	1	1	46425	30	0			
3	1	85	24	35	3,500	1	1	46425	35	0			
3	1	85	24	25	3,000	1	1	46625	25	0			
3	1	85	24	30	3,000	1	1	46625	30	0			
3	1	85	24	35	3,640	1	1	46625	35	0			

Type	Description	Locking points	Throws	Centre Distance	Faceplate	Backset	Unit weight 	Pieces 	ITEM			
									Type	Dim.	Hand	Fin.




- Black lacquered steel adjustable U-shaped faceplate
24 x 7 mm., 2.600 mm.
upper adjustment 650 mm.
lower adjustment 150 mm.
- 11 to 17 mm. adjustable latch and piston
- 2 lateral dead-bolts
- Top extended bolt
- Nylon faceplate cover plugs

2	1	85	24	25	3,400	1	1	46435	25	0
2	1	85	24	30	3,420	1	1	46435	30	0
2	1	85	24	35	3,440	1	1	46435	35	0




- Black lacquered steel adjustable U-shaped faceplate
24 x 7 mm., 2.600 mm.
upper adjustment 650 mm.
lower adjustment 150 mm.
- 11 to 17 mm. adjustable latch and piston
- 1 lateral dead-bolt
- Vertical extended bolts
- Nylon faceplate cover plugs

1	1	85	24	25	3,500	1	1	46445	25	0
1	1	85	24	30	3,500	1	1	46445	30	0
1	1	85	24	35	3,240	1	1	46445	35	0

Type	Description	Locking points Throws	Centre Distance	Faceplate Backset	Unit weight Kg	Pieces	ITEM					
							Type	Dim.	Hand	Fin.	Pers. Spec.	
 <ul style="list-style-type: none"> • Black lacquered steel adjustable U-shaped faceplate 24 x 7 mm., 2.600 mm. upper adjustment 650 mm. lower adjustment 150 mm. • 2.5 to 16.5 mm. adjustable roller • 3 lateral dead-bolts • Nylon faceplate cover plugs 		3	1	24	25	3,600	1	1	46450	25	0	
		3	1	24	30	3,500	1	1	46450	30	0	
		3	1	24	35	3,640	1	1	46450	35	0	
			3	1	24	25	3,600	1	1	46650	25	0
		<ul style="list-style-type: none"> • Stainless steel adjustable U-shaped faceplate 24 x 7 mm., 2.300 mm. upper adjustment 350 mm. lower adjustment 150 mm. • 2.5 to 16.5 mm. adjustable roller • 3 lateral dead-bolts 	3	1	24	30	3,620	1	1	46650	30	0
			3	1	24	35	3,640	1	1	46650	35	0

Type	Description	Locking points	Throws	Centre Distance	Faceplate	Backset	Unit weight 	Pieces 	ITEM			
									Type	Dim.	Hand	Fin.




- Black lacquered steel adjustable flat faceplate 24 x 3 mm., 2.600 mm.
upper adjustment 650 mm.
lower adjustment 150 mm.
- 10.5 to 16.5 mm. adjustable latch and piston
- 3 lateral dead-bolts
- Nylon faceplate cover plug

3	1	85	24	25	3,500	1	1	16525	25	0
3	1	85	24	30	3,500	1	1	16525	30	0
3	1	85	24	35	3,500	1	1	16525	35	0

- Stainless steel adjustable flat faceplate 24 x 7 mm., 2.300 mm.
upper adjustment 350 mm.
lower adjustment 150 mm.
- 10.5 to 16.5 mm. adjustable latch and piston
- 3 lateral dead-bolts


3	1	85	24	25	3,780	1	1	16725	25	0
3	1	85	24	30	3,800	1	1	16725	30	0
3	1	85	24	35	3,820	1	1	16725	35	0



- Black lacquered steel adjustable flat faceplate 24 x 3 mm., 2.600 mm.
upper adjustment 650 mm.
lower adjustment 150 mm.
- 3 lateral dead-bolts
- Nylon faceplate cover plugs

3	1	24	25	3,600	1	1	46520	25	0
3	1	24	30	3,620	1	1	46520	30	0
3	1	24	35	3,640	1	1	46520	35	0

Type	Description	Locking points	Throws	Centre Distance	Faceplate	Backset	Unit weight 	Pieces 	ITEM			
									Type	Dim.	Hand	Fin.




- Black lacquered steel adjustable flat faceplate
24 x 3 mm., 2.600 mm.
upper adjustment 650 mm.
lower adjustment 150 mm.
- 11 to 17 mm. adjustable latch
- 3 lateral dead-bolts
- Nylon faceplate cover plugs

3	1	85	24	25	3,600	1	1	46525	25	0
3	1	85	24	30	3,500	1	1	46525	30	0
3	1	85	24	35	3,500	1	1	46525	35	0

- Stainless steel adjustable flat faceplate
24 x 3 mm., 2.300 mm.
upper adjustment 350 mm.
lower adjustment 150 mm.
- 11 to 17 mm. adjustable latch
- 3 lateral dead-bolts

3	1	85	24	25	3,600	1	1	46725	25	0
3	1	85	24	30	3,620	1	1	46725	30	0
3	1	85	24	35	3,640	1	1	46725	35	0



- Black lacquered steel adjustable flat faceplate
24 x 3 mm., 2.600 mm.
upper adjustment 650 mm.
lower adjustment 150 mm.
- 2.5 to 16.5 mm. adjustable roller
- 3 lateral dead-bolts
- Nylon faceplate cover plugs

3	1	24	25	3,500	1	1	46550	25	0
3	1	24	30	3,500	1	1	46550	30	0
3	1	24	35	3,500	1	1	46550	35	0

- Stainless steel adjustable flat faceplate
24 x 3 mm., 2.300 mm.
upper adjustment 350 mm.
lower adjustment 150 mm.
- 2.5 to 16.5 mm. adjustable roller
- 3 lateral dead-bolts

3	1	24	25	3,600	1	1	46750	25	0
3	1	24	30	3,620	1	1	46750	30	0
3	1	24	35	3,640	1	1	46750	35	0