



Technical features:

- Zinc plated case
- Zinc plated faceplate
- Brass latch, roller and bolt
- Current absorption 1,4 A
- Voltage 12 V ac CE

Supplied as standard:

- Cylinder fixing screws
- Instruction sheet (if this is provided for)

On request:

- Specific striking plates (see Vademecum)

Hand:

0 = Non-handed

1 = R.H. inwards

2 = L.H. inwards

Cylinder to be ordered separately



Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight 	Pieces 	ITEM			
								Type	Dim.	Hand	Fin. Pers. Spec.
	• Dead-locking latch	16	15	0,360	1	1	14020	15	1		
		16	15	0,355	1	1	14020	15	2		
		16	18	0,371	1	1	14020	18	1		
		16	18	0,365	1	1	14020	18	2		
	• Dead-locking latch	20	15	0,381	1	1	14021	15	1		
		20	15	0,381	1	1	14021	15	2		
		20	18	0,394	1	1	14021	18	1		
		20	18	0,394	1	1	14021	18	2		
	• Nickel-plated faceplate • Nickel-plated dead-bolt only • Nickel-plated steel flat striker item 1.07027.00.0	1	20	16	0,265	12	1	44210	16	0	
	• Case height 85 mm. • Cylinder activated non-handed latch	16	15	0,140	12	1	44217	15	0		
	• Case height 85 mm. • Cylinder activated non-handed latch	20	15	0,150	12	1	44218	15	0		
	• 4.5 mm. extra protruding dead-bolt and non-handed latch • Latch can be activated by key	1	69	14	25	0,365	12	1	44219	25	0
		1	69	14	30	0,410	12	1	44219	30	0
	• Dead-bolt and non-handed latch • Latch can be activated by key except for locks with E=15 and 18	1	69	16	15	0,290	12	1	44220	15	0
		1	69	16	18	0,310	12	1	44220	18	0
		1	69	16	25	0,350	12	1	44220	25	0
		1	69	16	30	0,390	12	1	44220	30	0
		1	69	16	35	0,425	12	1	44220	35	0
		1	69	14,7	35	0,450	12	1	44220	35	0 00 EN
	• Dead-bolt and non-handed latch • Latch can be activated by key except for locks with E=15 and 18	1	69	20	15	0,305	12	1	44221	15	0
		1	69	20	18	0,328	12	1	44221	18	0
		1	69	20	25	0,360	12	1	44221	25	0
		1	69	20	30	0,405	12	1	44221	30	0
		1	69	20	35	0,430	12	1	44221	35	0

Type	Description	Throws	Centre Distance	Faceplate	Backset	Unit weight Kg	Pieces	ITEM						
								Type	Dim.	Hand	Fin.	Pers. Spec.		
	<ul style="list-style-type: none"> • 4.5 mm. extra protruding dead-bolt and non-handed latch • Latch can be activated by key except for locks with E=25 	2	69	14	25	0,390	12	1	44224	25	0			
		2	69	14	30	0,434	12	1	44224	30	0			
	<ul style="list-style-type: none"> • Dead-bolt and non-handed latch • Latch can be activated by key except for locks with E=15-18-25 	2	69	16	15	0,318	12	1	44225	15	0			
		2	69	16	18	0,335	12	1	44225	18	0			
		2	69	16	25	0,374	12	1	44225	25	0			
		2	69	16	30	0,416	12	1	44225	30	0			
		2	69	16	35	0,454	12	1	44225	35	0			
		2	69	14	35	0,450	12	1	44225	35	0	00	EN	
	<ul style="list-style-type: none"> • ABITHAL PROFILE ROUND VERSION • Dead-bolt and non-handed latch • Latch can be activated by key 													
		<ul style="list-style-type: none"> • Dead-bolt and non-handed latch • Latch can be activated by key except for locks with E=15-18-25 	2	69	20	15	0,336	12	1	44226	15	0		
			2	69	20	18	0,355	12	1	44226	18	0		
			2	69	20	25	0,385	12	1	44226	25	0		
			2	69	20	30	0,433	12	1	44226	30	0		
	2		69	20	35	0,465	12	1	44226	35	0			
	<ul style="list-style-type: none"> • Case height 85 mm. • Handle activated non-handed latch 													
	<ul style="list-style-type: none"> • Case height 85 mm. • Handle activated non-handed latch 													
	<ul style="list-style-type: none"> • Adjustable dead-bolt and roller 	1	16	15	0,265	12	1	44230	15	0				
		1	16	18	0,292	12	1	44230	18	0				
		1	16	25	0,340	12	1	44230	25	0				
		1	16	30	0,375	12	1	44230	30	0				
		1	16	35	0,408	12	1	44230	35	0				
	<ul style="list-style-type: none"> • Adjustable dead-bolt and roller 	1	20	15	0,293	12	1	44231	15	0				
		1	20	18	0,313	12	1	44231	18	0				
		1	20	25	0,359	12	1	44231	25	0				
		1	20	30	0,391	12	1	44231	30	0				
		1	20	35	0,426	12	1	44231	35	0				
		<ul style="list-style-type: none"> • Adjustable dead-bolt and roller 	2	16	15	0,300	12	1	44235	15	0			
			2	16	18	0,320	12	1	44235	18	0			
			2	16	25	0,366	12	1	44235	25	0			
2			16	30	0,398	12	1	44235	30	0				
2			16	35	0,434	12	1	44235	35	0				
<ul style="list-style-type: none"> • Adjustable dead-bolt and roller 		2	20	18	0,340	12	1	44236	18	0				
		2	20	25	0,415	12	1	44236	25	0				
		2	20	30	0,419	12	1	44236	30	0				
		2	20	35	0,454	12	1	44236	35	0				
	<ul style="list-style-type: none"> • Case height 70 mm. • Adjustable roller 													
	<ul style="list-style-type: none"> • Case height 70 mm. • Adjustable roller 													

Type	Description	Throws	Centre Distance	Faceplate Backset	Unit weight Kg	Pieces	ITEM					
							Type	Dim.	Hand	Fin.	Pers. Spec.	
	• Dead-bolt only	1	16	15	0,180	12	1	44240	15	0		
		1	16	18	0,199	12	1	44240	18	0		
		1	16	25	0,234	12	1	44240	25	0		
		1	16	30	0,261	12	1	44240	30	0		
		1	16	35	0,290	12	1	44240	35	0		
	• Dead-bolt only	1	20	15	0,195	12	1	44241	15	0		
		1	20	18	0,211	12	1	44241	18	0		
		1	20	25	0,246	12	1	44241	25	0		
		1	20	30	0,273	12	1	44241	30	0		
		1	20	35	0,300	12	1	44241	35	0		
	• Dead bolt only (without protrusion)	2	20	15	0,175	12	1	44242	15	0		
		• Dead-bolt only	2	16	15	0,210	12	1	44245	15	0	
			2	16	18	0,225	12	1	44245	18	0	
			2	16	25	0,256	12	1	44245	25	0	
			2	16	30	0,286	12	1	44245	30	0	
2			16	35	0,315	12	1	44245	35	0		
• Dead-bolt only		2	20	15	0,220	12	1	44246	15	0		
		2	20	18	0,239	12	1	44246	18	0		
		2	20	25	0,274	12	1	44246	25	0		
		2	20	30	0,300	12	1	44246	30	0		
		2	20	35	0,329	12	1	44246	35	0		
		• Nickel-plated laminar steel	1	20	16	0,255	12	1	45010	16	0	
		• Zinc plated steel flat striker item 1.07028.00.0										
		• Nickel-plated laminated steel hook with throw	1	20	16	0,260	12	1	45012	16	0	
		• Nickel-plated steel guide pin • Zinc plated steel flat striker item 1.07028.05.0										
		• Nickel-plated laminated steel hook with latch bolt	1	20	16	0,260	12	1	45027	16	0	
	• Dead locking latch • Nickel-plated steel guide pin • Zinc plated steel flat striker item 1.07028.05.0											