



Technical features:

- Case height 78 mm
- Zinc plated case
- Stainless steel faceplate
- Nickel-plated steel dead-bolt
- Nickel-plated roller and reversible latch
- Drill resistant protection plate
- Electrical and mechanical versions are interchangeable
- Current absorption 1,7 A
- Voltage 12 V ac CE

Supplied as standard:







- 3 keys item 1.00100.00.0 or item 1.00102.00.0
- Set of nylon key guide escutcheons item 1.06123.03.0

Rose fastening screws:

- length 60 mm for the version with key item 1.00100.00.0
- length 75 mm for the version with key item 1.00102.00.0
- Set of nylon faceplate spacers item 1.06141.65.0
- Threaded extended bolts connectors
- Lock fixing screws
- Instruction sheet

On request:

- Specific striking plates
- Mechanical control button item 1.06110.10.0

Type	Description	Key item	Throws	Centre Distance	Faceplate Backset	Unit weight Kg	Pieces	ITEM			
								Type	Dim.	Hand	Fin. Pers. Spec.
	<ul style="list-style-type: none"> • Dead-bolt and latch • 12 to 18 mm. adjustable latch and piston • Dead-locking latch • Hold-open latch 	 1 00100 00 1	4	67	22 90	1,330	1	1	17352	90	0
			4	67	22 100	1,385	1	1	17352	10	0
	<ul style="list-style-type: none"> • Dead-bolt and latch • 12 to 18 mm. adjustable latch and piston • Dead-locking latch • Hold-open latch • Pre-arranged for additional locking points • Threaded pivots for fixing extended bolts • ON REQUEST: Internal ragged extended bolts item 1.06441.00.0 Internal straight extended bolts item 1.06441.10.0 External bolt connectors item 1.06442.00.0 Extended bolts operated by internal rods item 1.06443.00.0 Extended bolts operated by external rods item 1.06443.05.0 	 1 00100 00 1	4	67	22 90	1,400	1	1	17357	90	0
			4	67	22 100	1,463	1	1	17357	10	0
			4	67	22 90	1,410	1	1	17357	91	0
			4	67	22 100	1,450	1	1	17357	11	0
	<ul style="list-style-type: none"> • Dead-bolt and latch • 11 to 17 mm. adjustable latch 	 1 00100 00 1	4	67	22 90	1,210	12	1	57352	90	0
			4	67	22 100	1,316	12	1	57352	10	0

Type	Description	Key item	Throws	Centre Distance	Faceplate	Backset	Unit weight 	Pieces 	ITEM				
									Type	Dim.	Hand	Fin.	Pers. Spec.
	<ul style="list-style-type: none"> • Dead-bolt and latch • 11 to 17 mm. adjustable latch • Pre-arranged for additional locking points • Threaded pivots for fixing extended bolts • ON REQUEST: Internal ragged extended bolts item 1.06441.00.0 Internal straight extended bolts item 1.06441.10.0 External bolt connectors item 1.06442.00.0 Extended bolts operated by internal rods item 1.06443.00.0 Extended bolts operated by external rods item 1.06443.05.0 	 1 00100 00 1	4	67	22	90	1,275	12	1	57357	90	0	
			4	67	22	100	1,340	12	1	57357	10	0	
	<ul style="list-style-type: none"> • Dead-bolt and roller • 2 to 14.5 mm. adjustable roller 	 1 00102 00 1	4	67	22	90	1,305	12	1	57357	91	0	
			4	67	22	100	1,355	12	1	57357	11	0	
	<ul style="list-style-type: none"> • Dead-bolt and roller • 2 to 14.5 mm. adjustable roller • Pre-arranged for additional locking points • Threaded pivots for fixing extended bolts • ON REQUEST: Internal ragged extended bolts item 1.06441.00.0 Internal straight extended bolts item 1.06441.10.0 External bolt connectors item 1.06442.00.0 Extended bolts operated by internal rods item 1.06443.00.0 Extended bolts operated by external rods item 1.06443.05.0 	 1 00100 00 1	4	22	90	1,225	12	1	57365	90	0		
			4	22	100	1,250	12	1	57365	10	0		
	<ul style="list-style-type: none"> • Dead-bolt only 	 1 00100 00 1	4	22	90	1,129	12	1	57370	90	0		
			4	22	100	1,168	12	1	57370	10	0		

Type	Description	Key item	Throws	Centre Distance	Faceplate Backset	Unit weight Kg	Pieces	ITEM				
								Type	Dim.	Hand	Fin.	Pers. Spec.
	<ul style="list-style-type: none"> • Dead-bolt only • Pre-arranged for additional locking points • Threaded pivots for fixing extended bolts • ON REQUEST: <ul style="list-style-type: none"> Internal ragged extended bolts item 1.06441.00.0 Internal straight extended bolts item 1.06441.10.0 External bolt connectors item 1.06442.00.0 Extended bolts operated by internal rods item 1.06443.00.0 Extended bolts operated by external rods item 1.06443.05.0 	 1 00100 00 1	4	22	90	1,185	12	1	57375	90	0	
			4	22	100	1,250	12	1	57375	10	0	

