



Technical features:

- Zinc-plated steel case
- Steel deadbolts with 25 mm travel (for the series 41600, 41620 and 41650, 24 mm travel)
- Brass cylinder

Supplied as standard:


- 3 keys
- ITEMS 41010 - 41110 - 41111:
inside: 1 key item 1.01310.00.2
outside: 2 keys item 1.01330.00.1
- ITEMS 41210 - 41220 - 41221 - 41230 - 41231 - 41310 - 41311 - 41320:
inside: 1 key item 1.01310.00.2
outside: 2 keys item 1.01320.00.1

- ITEMS 41410 - 41420 - 41421:
inside: 1 key item 1.01320.00.2
outside: 2 keys item 1.01330.00.1
- ITEMS 41510 - 41525 - 41526:
2 keys item 1.01060.10.0
- ITEMS 41600 - 41650:
2 keys item 1.01070.10.1
- Cylinder fixing screw (series 41620)

Hand:


- 0 = Non-handed
- 1 = R.H.
- 2 = L.H

| Type | Description | Cylinder | L | A | B | S | Throws | Backset | Unit weight Kg | Pieces | ITEM | | | |
|------|-------------|----------|---|---|---|---|--------|---------|-------------------|--------|------|------|------|------------|
| | | | | | | | | | | | Type | Dim. | Hand | Fin. Spec. |




• Central application

| | | | | | | | | | |
|--------------|-----|----|------|------|---|----|-------|---|--------------|
| 1 02544 14 0 | 160 | 55 | 11,5 | 13,0 | 2 | 80 | 0,508 | 2 | 1 41010 80 0 |
| 1 02544 15 0 | 155 | 55 | 6,5 | 20,0 | 2 | 78 | 0,551 | 2 | 1 41210 78 0 |
| 1 02544 15 0 | 155 | 55 | 9,5 | 17,0 | 2 | 78 | 0,540 | 2 | 1 41320 78 0 |
| 1 02544 10 0 | 155 | 55 | 6,0 | 15,0 | 2 | 78 | 0,518 | 2 | 1 41410 78 0 |




• Lateral application

| | | | | | | | | | |
|--------------|-----|----|------|------|---|----|-------|---|--------------|
| 1 02544 14 0 | 120 | 55 | 11,5 | 15,0 | 2 | 78 | 0,420 | 2 | 1 41110 60 1 |
| 1 02544 14 0 | 120 | 55 | 11,5 | 13,0 | 2 | 60 | 0,424 | 2 | 1 41110 60 2 |
| 1 02544 15 0 | 155 | 55 | 6,5 | 20,0 | 2 | 78 | 0,530 | 2 | 1 41220 78 1 |
| 1 02544 15 0 | 155 | 55 | 6,5 | 20,0 | 2 | 78 | 0,530 | 2 | 1 41220 78 2 |
| 1 02544 15 0 | 155 | 55 | 6,5 | 20,0 | 2 | 78 | 0,527 | 2 | 1 41230 78 1 |
| 1 02544 15 0 | 155 | 55 | 6,5 | 20,0 | 2 | 78 | 0,527 | 2 | 1 41230 78 2 |
| 1 02544 15 0 | 155 | 55 | 9,5 | 17,0 | 2 | 78 | 0,512 | 2 | 1 41310 78 1 |
| 1 02544 15 0 | 155 | 55 | 9,5 | 17,0 | 2 | 78 | 0,512 | 2 | 1 41310 78 2 |
| 1 02544 10 0 | 155 | 55 | 6,0 | 15,0 | 2 | 78 | 0,490 | 2 | 1 41420 78 1 |
| 1 02544 10 0 | 155 | 55 | 6,0 | 15,0 | 2 | 78 | 0,498 | 2 | 1 41420 78 2 |









• Pair of locks with lateral application
(1 pc.rh, 1 pc.lh)

| | | | | | | | | | |
|--------------|-----|----|------|------|---|----|-------|---|--------------|
| 1 02544 14 0 | 120 | 55 | 11,5 | 13,0 | 2 | 60 | 0,848 | 2 | 1 41110 60 0 |
| 1 02544 15 0 | 155 | 55 | 6,5 | 20,0 | 2 | 78 | 1,060 | 2 | 1 41220 78 0 |
| 1 02544 15 0 | 155 | 55 | 6,5 | 20,0 | 2 | 78 | 1,054 | 2 | 1 41230 78 0 |
| 1 02544 15 0 | 155 | 55 | 9,5 | 17,0 | 2 | 78 | 1,024 | 2 | 1 41310 78 0 |
| 1 02544 10 0 | 155 | 55 | 6,0 | 15,0 | 2 | 78 | 0,996 | 2 | 1 41420 78 0 |



- Pair of locks with lateral application
(1 pc.rh, 1 pc.lh)
- Keyed alike (KA)
- 3 keys per pair

| | | | | | | | | | |
|--------------|-----|----|------|------|---|----|-------|---|--------------|
| 1 02544 14 0 | 120 | 55 | 11,5 | 13,0 | 2 | 60 | 0,800 | 2 | 1 41111 60 0 |
| 1 02544 15 0 | 155 | 55 | 6,5 | 20,0 | 2 | 78 | 1,060 | 2 | 1 41221 78 0 |
| 1 02544 15 0 | 155 | 55 | 6,5 | 20,0 | 2 | 78 | 1,054 | 2 | 1 41231 78 0 |
| 1 02544 15 0 | 155 | 55 | 9,5 | 17,0 | 2 | 78 | 1,024 | 2 | 1 41311 78 0 |
| 1 02544 10 0 | 155 | 55 | 6,0 | 15,0 | 2 | 78 | 0,940 | 2 | 1 41421 78 0 |

| Type | Description | Cylinder | Cylinder | | | | Throws | Backset | Unit weight | Pieces | ITEM | | | | | | |
|--|--|----------|----------|-----|------|---|--------|---------|-----------------|------------|-------|------|------|------|-------|-------|--|
| | | | L | A | B | S | | | | | Type | Dim. | Hand | Fin. | Pers. | Spec. | |
|   | <ul style="list-style-type: none"> • Central application • Straight deadbolt • 2 Ø 9 mm pins | 155 | 55 | 5,5 | 15,0 | 2 | 78 | 0,525 | 12 | 1 | 41510 | 78 | 0 | | | | |
| | <ul style="list-style-type: none"> • Version with fixing plate assembled • Central application • Straight deadbolt • 2 Ø 9 mm pins | 155 | 55 | 5,5 | 15,0 | 2 | 78 | 0,518 | 12 | 1 | 41510 | 78 | 0 | 00 | TC | | |
| | <ul style="list-style-type: none"> • Version with pins and fixing plate assembled • Central application • Straight deadbolt • 2 Ø 9 mm pins | 155 | 55 | 5,5 | 15,0 | 2 | 78 | 0,518 | 12 | 1 | 41510 | 78 | 0 | 00 | ZQ | | |
|   | <ul style="list-style-type: none"> • Lateral application • Bent deadbolt • 1 Ø 9 mm pins | 155 | 55 | 5,5 | 15,0 | 2 | 78 | 0,445 | 12 | 1 | 41525 | 78 | 1 | | | | |
| | | 155 | 55 | 5,5 | 15,0 | 2 | 78 | 0,490 | 12 | 1 | 41525 | 78 | 2 | | | | |
|   | <ul style="list-style-type: none"> • Pair of locks with lateral application (1 pc. RH, 1 pc. LH) • Bent deadbolt • 2 Ø 9 mm pins | 155 | 55 | 5,5 | 15,0 | 2 | 78 | 0,800 | 6 | 1 | 41525 | 78 | 0 | | | | |
| | <ul style="list-style-type: none"> • Pair of locks with lateral application (1 pc. RH, 1 pc. LH) • Bent deadbolt • Keyed alike (KA) • 3 keys per pair • 2 Ø 9 mm pins | 155 | 55 | 5,5 | 15,0 | 2 | 78 | 0,875 | 6 | 1 | 41526 | 78 | 0 | | | | |

| Type | Description | Cylinder | Cylinder | | | | Throws | Backset | Unit weight | Pieces | ITEM | | | | | | | |
|------|--|----------|----------|----|------|------|--------|---------|-----------------|------------|-------|-------|------|------|-------|-------|--|--|
| | | | L | A | B | S | | | | | Type | Dim. | Hand | Fin. | Pers. | Spec. | | |
| | <ul style="list-style-type: none"> • FOR SWING DOORS • Top lock • OPERATION: from the inside and the outside: opening via the handle, from the outside: key locking, from the inside: lever unlocking • ON REQUEST: KA (Keyed Alike) system | | 155 | 55 | 15,0 | 1 | | 0,462 | 12 | 1 | 41600 | 00 | 0 | | | | | |
| | <ul style="list-style-type: none"> • FOR SWING DOORS • Top lock • European profile cylinders to order separately • OPERATION: from the inside and the outside: opening via the handle, from the outside: key locking, from the inside: lever unlocking • ON REQUEST: Cylinder fixing screws | | 155 | 55 | 15,0 | 1 | | 0,383 | 12 | 1 | 41620 | 00 | 0 | | | | | |
| | <ul style="list-style-type: none"> • FOR EXTENSIBLE GATES • Top and bottom locks • European profile cylinders to order separately • OPERATION: from the outside: with key only • ON REQUEST: KA (Keyed Alike) system | | 102 | 26 | 22,0 | 16,0 | 2 | 68 | 0,300 | 12 | 1 | 41650 | 00 | 0 | | | | |