









Technical features:

- Zinc plated steel faceplate
- Zinc plated steel case
- Zinc plated steel latch
- 9 mm. split follower
- Can be combined with the panic exit devices series 59600 and 59711.00.0.00.00.FR

Hand:

0 = Non-handed

Cylinder to be ordered separately



Mito Panic

Туре

Description



72 24 65








1 13110 65 0

Type Dim. Hand Fin. Spec.



• Latch only

• 12 V dc - 800 mA

• OPERATION:

Inside: with the handle or the key Outside: with the electrically operated handle and/or the key



• 12 V dc - 800 mA

• OPERATION:

For pull panic doors

0,980



• Latch only

72	24	65	0,980	I	ı	13160 65 1
72	24	65	0,980	1	1	13160 65 2



• Latch bolt only

• OPERATION:

Inside: panic exit device and/or key Outside: the key activates and disactivates handle and

Handle withdraws latch only if activated by the key

72	72	24	65	0,848	6	1	43110 65
----	----	----	----	-------	---	---	----------



• Dead-bolt and latch

• 15 mm throw

• OPERATION:

Inside: panic exit device and/or key Outside: the key withdraws latch and dead-bolt

1 43120 65 0 72 24 65 0,853



• Dead-bolt and latch

• 15 mm throw


• OPERATION:

Inside: panic exit device and/or key Outside: the key withdraws latch and dead-bolt, latch withdrawn by handle

6 1 **43130 65 0** 1 72 24 65 0,876



Type Description States and the post of th



• Latch only

• Pre-arranged for additional locking points

• ON REQUEST:

Zinc plated extended bolts item 1.07091.50.0 Set of zinc plated side latches item 1.07090.50.0

• OPERATION:

Inside: panic exit device and/or key Outside: the key activates and disactivates handle and withdraws latch Handle withdraws latch only if activated by the key

72 24 65

0,850

72 24 65 1,750

6 1 **43115 65 0**

1 43114 65 0

Latches only

- 3 locking points
- OPERATION:

Inside: panic exit device and/or key
Outside: the key activates and disactivates handle and
withdraws latches
Handle withdraws latches only if activated by the key



• FOR SECONDARY LEAF OF A DOUBLE DOOR

 A latch only lock to be installed on main leaf, item 1.43110.65.0 or 1.43115.65.0

- Rod extension 17 mm
- OPERATION:

Inside: panic exit device

• ON REQUEST:

Extended bolts item 1.07088.03.0 Automatic dogging device 1.07089.50.0

24 65

24 95

0,858

1,150

1 43190 65 0

1 43190 95 0

PANIC FUNCTION CYLINDER MORTICE LOCKS



Type Description See that Desc



- FOR SECONDARY LEAF OF A DOUBLE DOOR
- DOUBLE FUNCTIONEMENT VERSION
- A latch only lock to be installed on main leaf, item 1.43110.65.0 or 1.43115.65.0
- Rod's forward stroke 17 mm
- OPERATION: Inside:panic exit device
- ON REQUEST:
 Extended bolts item 1.07088.03.0
 Automatic dogging device 1.07089.50.0

1	24	65	0,858	1 1	43191 65 0	
1	24	95	1,000	1 1	43191 95 0	