

## DICHIARAZIONE DI PRESTAZIONE DECLARATION OF PERFORMANCE

Ai sensi del REGOLAMENTO (UE) N. 305/2011

n. 47425648

### 1. Codice di identificazione unico del prodotto-tipo:

*Unique identification code of the product-type:*

Dispositivi antipánico per uscite di sicurezza azionati mediante barra orizzontale Serie "MATIC"

Panic exit devices: "MATIC"

### 2. Numero di tipo ai sensi dell'articolo 11, paragrafo 4:

*Type number as required pursuant to Article 11(4):*

System CISA Series "MATIC" Panic exit device

Series "FAST PUSH": 1.59607-10-0-xx-xx, 1.59617-12-0-xx-xx,

MATIC panic locks: 1.4PY10-xx-0-xx-zz, 1.4PY30-xx-0-xx-zz, 1.1PY10-xx-0-xx-zz,  
1.1PY30-xx-0-xx-zz,

Y=0,1,2,3,4; xx=0,1,2,3,4,5.

Barre / bars: 1.07007-xx-0

Comando esterno (Outside access device): 1.07070-xx-0.

Accessori (Accessories): 1.06463-xx-0-xx, 1.06465-xx-0-xx, 1.06461-xx-0-xx, 1.06460-05-0-xx, 1.07076-71-0-xx.

### 3. Uso o usi previsti del prodotto da costruzione, conformemente alla relativa specifica tecnica armonizzata, come previsto dal fabbricante:

*Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:*

Dispositivi antipánico per uscite di sicurezza da utilizzare su porte sulla via dell'esodo  
Exit panic devices to be used for locked doors on escape routes

### 4. Nome, denominazione commerciale registrata o marchio registrato e indirizzo del fabbricante ai sensi dell'articolo 11, paragrafo 5:

*Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):*

CISA S.p.A – Via Oberdan 42, 42018 Faenza (RA) Italy



Essential Characteristic	Performance	Harmonised technical specification
<b>Ability to release (for locked doors on escape routes)</b>		
Release function	$\leq 1$ s	EN1125:2008 par. 4.1.2
Panic exit device mounting	Pass	EN1125:2008 par. 4.1.3
Exposed edges and corners	$\geq 0,5$ mm	EN1125:2008 par. 4.1.5
Double doorset	NA	EN1125:2008 par. 4.1.7
Bar installation	$Z \leq 150$ mm	EN1125:2008 par. 4.1.9
Bar length	$\geq 60$ % of the door width	EN1125:2008 par. 4.1.10
Bar projection	$W < 100$ mm	EN1125:2008 par. 4.1.11
Bar end	Pass	EN1125:2008 par. 4.1.12
Operating bar face	$V > 18$ mm	EN1125:2008 par. 4.1.13
Test rod	Pass	EN1125:2008 par. 4.1.14
Door face gap	NA	EN1125:2008 par. 4.1.15
Accessible gap	Pass	EN1125:2008 par. 4.1.16
Door free movement	Pass	EN1125:2008 par. 4.1.17
Top vertical bolt	Pass	EN1125:2008 par. 4.1.18
Keepers	Pass	EN1125:2008 par. 4.1.20
Keepers dimensions	$H \leq 15$ mm $M \leq 45^\circ$ $P \leq 3$ mm	EN1125:2008 par. 4.1.21
Door mass and dimensions	Grade 6	EN1125:2008 par.4.1.23 6.3.2 6.3.4 6.3.5 6.3.6 6.3.8
Outside access device	Pass	EN1125:2008 par. 4.1.24 6.3.2
Release forces	$\leq 80$ N e/and $\leq 220$ N under pressure	EN1125:2008 par.4.2.2 6.3.2
Security requirement	Grade 2	EN1125:2008 par. 4.2.3
<b>Durability of ability to release(for locked doors on escape routes)</b>		
Corrosion resistance	Grade 4; 240h salt spray fog	EN1125:2008 par. 4.14, 4.2.9
Temperature range	( -10°C / +60° C) 50 % in excess	EN1125:2008 par. 4.1.3
Covers for vertical rods	If present, they can be removed only by means of a specific tool.	EN1125:2008 par. 4.1.19, 4.2.6
Lubrication	20 000 cycles	EN1125:2008 par. 4.1.22 6.3.4
Re-engagement force	$\leq 50$ N	EN1125:2008 par. 4.2.3 6.3.3

Durability	Grade 7; 200000cycles	EN1125:2008 par.4.2.4 6.3.4
Abuse resistance – Horizontal bar	1000 N	EN1125:2008 par. 4.2.5 6.3.5
Abuse resistance – Vertical rod	NA	EN1125:2008 par. 4.2.6
<b>Self closing ability C against aging and degradation (for fire/smoke doors on escape routes)</b>		
Re-engagement force	Threshold (<= 50 N)	EN1125:2008 par. 4.2.3
<b>Durability of Self closing ability C against aging and degradation (for fire/smoke doors on escape routes)</b>		
Durability	Grade 7, 200000cycles	EN1125:2008 par. 4.2.4
Re-engagement force	Threshold (<= 50 N)	EN1125:2008 par. 4.2.3
<b>Resistance to fire E (integrity) and I (insulation)</b>		
Suitability of emergency exit devices for use on fire resisting doorsets assemblies – Additional requirements	Grade B	EN 1125:2008 par. 4.1.10; Annex B
<b>Dangerous substances</b>		
Control of dangerous substances	Pass	EN1125:2008 par. 4.1.25

**10. La prestazione del prodotto di cui ai punti 1 e 2 è conforme alla prestazione dichiarata di cui al punto 9.**

*The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.*

Si rilascia la presente dichiarazione di prestazione sotto la responsabilità esclusiva del fabbricante di cui al punto 4.

*This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.*

Firmato a nome e per conto del costruttore:

Signed for and on behalf of the manufacturer by:

.....Faenza (RA) 05/09/2022.....  
(luogo e data del rilascio)  
(place and date of issue)

Il Legale Rappresentante  
Legal Representative



(firma)  
(signature)